

GUANGZHOU LEY&SONS ENVIRONMENTAL TECHNOLOGY CO.,LTD



4.12 Fan Filter Unit(FFU)





Classification

Purification Equipment

Product Description

Fan Filter Unit(FFU)

***Product Introduction**

- 1. Stepless speed regulation design, requires no maintenance, features low vibration and low noise.
- 2. Before leaving the factory, each unit is scanned and tested with a dust particle counter in accordance with the international standard ISO14644-1 to ensure quality. It can be controlled in groups of thousands, reducing the failure rate.
- 3. High energy-efficiency ratio and generates very little heat, which further reduces the heat generation in the additional working environment area.
- 4. Especially suitable for assembling into ultra-clean production lines. It can be arranged for single-unit use according to process requirements, or multiple units can be connected in series to form a Class 100 flow assembly line.
- 5. Direct-drive high-efficiency centrifugal fan. The shell structure is made of materials such as stainless steel and galvalume sheet, which is light-weight, corrosion-resistant, rust-proof, and aesthetically pleasing.

%Size&Data





GUANGZHOU LEY&SONS ENVIRONMENTAL TECHNOLOGY CO.,LTD

Model		LJ-Q53	LJ-Q33	LJ-Q63	LJ-Q13	LJ-Q43	LJ-Q23
		5-HNA	5-HNA	5-HNA	5-HNA	5-HNA	5-HNA
		С	С	С	С	С	С
Modular size (W*L*H)		920*61 5*350	1175*5 75*350	1225*6 15*350	575*57 5*350	615*61 5*350	575*87 5*350
(mm)							
Static pressure box mate rial		A3 cold-rolled sheet with plastic spraying/ galvalume s					
		heet/ SS					
Airflow(m³/h)		900	1000	1200	500	600	800
Average velocity(m/s)		0.3~0.5					
Static pressure outside b ox(Pa)		190(10mmAq)					
Power(w)		115	115	115	173	240	115
Weight(kg)		31.5	37	40.5	21	23.5	27
Noise dB(1m below verti cal fine efficiency)		55~63					
Fine efficienc y filter spec.	Size(W*L*	915*61	1170*5	1220*6	570*57	610*61	570*87
	H)(mm)	0*69	70*69	10*69	0*69	0*69	0*69
	Efficiency	99.99%@0.3μm					
	Frame	Excellent aluminum					
	Initial pre	110Pa@0.45m/s					
	ssure loss						
Fan spec.	Power	220V/50Hz					
	Туре	Aluminum turbine fan					
	Vibration coefficient	0.2~0.5					

Besides the size above, custom size acceptable.

Related Products

